



VIN-LOX—00-100

Masonry Patching Compound—Knife Smooth Grade

Data Sheet

Product Description	Application	Characteristics
<p>VIN-LOX elastomeric patching compound KNIFE GRADE SMOOTH # 00-100 is an excellent elastomeric patching and water proofing material for repairing cracks in stucco and other masonry surfaces. A high quality acrylic polymer product, it will maintain a high level of flexibility on aging. Masonry patching compound is designed for above grade use and will adhere to virtually any clean damp or dry surface. Formulated to protect against the severe weather conditions unique to Florida and Tropical climates, this patch has been used for years by leading professional painting contractors, building maintenance operators, waterproofing companies and home owners looking for the highest quality product at an economical price.</p> <p>Product Features</p> <ul style="list-style-type: none"> ◦ Designed for Tropical Climates ◦ Fills large & hairline cracks ◦ Resists wind driven rain ◦ Resists mildew ◦ Resists shrinking & cracking ◦ Soap and water cleanup ◦ Excellent adhesion ◦ Extremely flexible ◦ Easy to apply ◦ Lead and Mercury free ◦ Low odor <p>Recommended Uses</p> <p>For exterior plaster and masonry wall surfaces that require a flexible, durable patching material.</p> <p>Surface Preparation</p> <p>Allow "new" concrete to cure for 30 days before any application of patch. Do not apply to surfaces with alkali presence where pH is above 10. All surfaces must be firm and free of dirt, oil, grease, efflorescence, mildew and loose material. Unsound masonry must be wire brushed away or blasted for a firm surface. Prepare surface by removing all dirt, grease, loose particles, foreign material and mildew.</p>	<p>Over properly prepared surface, apply masonry patch by hand, brush or putty knife as it comes from the can, feathering edges to blend with surrounding areas. DO NOT THIN.</p> <ul style="list-style-type: none"> • Hairline cracks: Apply knife smooth patch over crack and smooth over with water-wetted knife, if necessary. • Major Cracks: Pack knife smooth patch in crack leaving excess crown. Smooth with water wetted putty knife or paint brush. <p>Settlement Cracks: If continued movement is expected, pack knife grade patching into crack in two (2) stages. Fill cracks approximately one-half and allow it to consolidate for one (1) day. Pack remaining opening of crack and allow patching compound to crown above adjoining surfaces.</p> <p>Spreading Rate</p> <p>On primed wood and masonry up to 400 square feet per gallon. Depending on previous color, surface porosity and application methods, coverage can vary greatly.</p> <p>Drying Time</p> <p>Dries to the touch in 30 minutes. May be recoated after 4 hours. Drying times may vary depending on temperature, humidity.</p> <p>Clean Up</p> <p>Clean hand tools and equipment promptly with warm soapy water.</p>	<p>Characteristics</p> <p>Finish: Low Sheen Color: Standard White Type: Acrylic Latex Weight Per Gallon: 10.1 Pounds Weight Solids:(White) 76 ± 2% Volume Solids: (White) 65 ± 2% Vehicle by Weight: 55 ± 2% % Vehicle by Volume: 76 ± 2% % Pigment by Weight: 45 ± 2% % Pigment by Volume: 24 ± 2% VOC < 100 g/l</p> <p>Caution</p> <p>Keep From Freezing Do not take internally. Close container after each use. USE WITH ADEQUATE VENTILATION. KEEP CONTAINER OUT OF THE REACH OF CHILDREN.</p> <p>LIMITATION OF LIABILITY</p> <p>This information is based on technical data believed to be accurate and reliable, but is furnished without any express or implied warranties. Associated Paint, Inc. will replace such quantity of this paint that is proved to be defective. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED. Especially recommended for structures such as hotels, factories, hospitals, schools, offices, domestic homes, and commercial buildings subject to the harsh environment in tropical and subtropical climate areas.</p>