

# Associated Paint, Inc.



## 40-530.01 Sanding Sealer Data Sheet

<u>Characteristics:</u>	<u>Specifications</u>	<u>Surface Preparation</u>
<p>Sanding Sealer is a fast drying sealer that seals wood surfaces prior to the application of varnishes. Sanding Sealer dries quickly to a clear hard finish that's sands easily and holds out finish coats of varnish to give a smooth, even finish. For interior production work, Sanding Sealer may be left as is to give warm, low luster finish.</p> <p><b>Vehicle Type:</b> Vinyl Toluenated Alkyd</p> <p><b>FINISH:</b> Low Luster</p> <p><b>RECOMMENDED USES:</b></p> <ul style="list-style-type: none"> <li>• Interior Wood Surfaces</li> <li>• Prior to application of varnish</li> </ul> <p><b>NOTE:</b> Not recommended under polyurethane varnishes.</p>	<p><b>TINTING:</b> None</p> <p><b>THINNING:</b> Not Recommended</p> <p><b>DRYING TIME, @ 77° F, 50% RH:</b> Temperature &amp; Humidity Dependent</p> <p><b>Touch:</b> 1 hour  <b>Sand:</b> 2-3 hours  <b>Flash Point:</b> 50° F</p> <p><b>VOC:</b> &lt;550 g/l</p> <p><b>Weight Solids:</b> 36.4 ± 2%  <b>Volume Solids:</b> 30.7 ± 2%  <b>Weight Per Gallon:</b> 7.0 Lbs</p> <p><b>COVERAGE:</b> Apply Sanding Sealer at a rate of 300-350 sq. ft. per gallon.</p> <p><b>APPLICATION:</b> Apply 40-530 by brush, roller or low pressure spray. (1800-2000PSI and .017 tip).</p> <p style="text-align: center;"><b><u>Cleanup Information</u></b></p> <p>Clean spills, spatters, hands and tools immediately after use with mineral spirits. Follow manufacturer's safety recommendations when using mineral Sprits.</p>	<p><b>Wood</b> Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.</p> <p><b>Warning!</b> Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse affects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p>