

Associated Paint, Inc.



60-600.01 Acrylic Latex Stain Data Sheet

<u>Characteristics:</u>	<u>Surface Preparation</u>	<u>Surface Preparation</u>
<p>60-600 Acrylic Latex Stain is a solid coat stain formulated for exterior or interior use. Acrylic Stain goes on easily and dries to a uniform finish that resists mildew and fading.</p> <p>Vehicle Type: Acrylic</p> <p>FINISH: Low Sheen</p> <p>RECOMMENDED USES:</p> <ul style="list-style-type: none"> • Interior Bare Wood • Fencing • Shakes • Exterior new or previously finished wood • T III Plywood <p>TINTING: May be tinted to a wide range of colors with universal colorants in appropriate base.</p> <p>THINNING: Acrylic Stain may be reduced with up to 1 quart of water for varying degrees of shading.</p>	<p>Warning! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse affects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p> <p>Wood Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.</p> <p>Mildew Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the mildewed area for 10 minutes. Rinse thoroughly with water and allow the surface to dry prior to painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach water solution.</p>	<p>APPLICATION: Apply 60-600 by brush, roller or airless spray. (1800—2400psi and .017 tip)</p> <p>Important: All Stains tend to lap (dark lines where two freshly coated areas overlap). To minimize lapping:</p> <ul style="list-style-type: none"> • Do not stain in direct sun or on a hot surface. • Always stain into a wet edge. • Stain up and down vertical siding. • Use two coats on badly weathered or unfinished wood. • Apply a second coat when lap marks appear on first coat. <p>Cleanup Information Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.</p>
<p style="text-align: center;"><u>Specifications</u></p> <p>DRYING TIME, @ 77° F, 50% RH: Temperature & Humidity Dependent</p> <p>Touch: 1 Hour Recoat: 2 hours Flash Point: N/A</p> <p>VOC: <150 g/l</p> <p>Weight Solids: 44.0% ± 2% Volume Solids: 32.0% ± 2% Weight Per Gallon: 10.2 Lbs</p> <p>COVERAGE: 60-600 will cover up to 350 sq.ft per gallon @ 3.5 mils wet, 1.0 mils dry</p>		