

Associated Paint, Inc.



76-700.01

Acrylic Roof Coat—76-700 Flat White , 76-200 Deep Base, 76-300 Ultra Deep Base

Data Sheet

<u>Characteristics:</u>	<u>Specifications</u>	<u>Surface Preparation</u>
<p>Acrylic Roof Coat is formulated for Florida's tropical climate. Acrylic Roof Coat goes on easily and dries to a durable film that resists peeling, cracking, and blistering. Acrylic Roof Coat has excellent adhesion and color retention. White Acrylic Roof Coat can save energy by reflecting heat and UV rays. Acrylic Roof Coat is highly chalk and mildew resistant.</p> <p>Not recommended for flat roofs where ponding water is likely.</p> <p>Vehicle Type: Acrylic</p> <p>FINISH: Flat</p> <p>RECOMMENDED USES:</p> <ul style="list-style-type: none"> • Cement Tile Roofs • Slate Roofs • Bahamas & Bermuda Roofs • Gravel Roofs <p>TINTING: Acrylic Roof Coat may be tinted to a wide range of colors with universal colorants in the appropriate base.</p> <p>THINNING: Not recommended. However if thinning is necessary for spray application, add no more than ½ pint of water per gallon.</p> <p>DRYING TIME, @ 77° F, 50% RH: Temperature & Humidity Dependent</p> <p>Do not apply if air & surface temperature is below 50°F or if rain or heavy dew is expected within 24 hours. Do not apply in direct sunlight.</p> <p>Touch: 45 minutes Recoat: 2 hours Flash Point: N/A</p>	<p>VOC: < 150 g/l</p> <p>Weight Solids: 48.0 ± 2% Volume Solids: 31.0 ± 2% Weight Per Gallon: 11.2 Lbs</p> <p>COVERAGE: 76-700 will cover up to 300 sq.ft per gallon @ 4.0 mils wet, 1.5 mils dry</p> <p>APPLICATION: Apply 76-700 by brush, roller or airless spray (1800-2000 PSI and .017—.019 tip).</p>	<p>Mildew Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the mildewed area for 10 minutes. Rinse thoroughly with water and allow the surface to dry prior to painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach water solution.</p>
	<p style="text-align: center;"><u>Cleanup Information</u></p> <p>Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral sprits.</p> <p style="text-align: center;"><u>Surface Preparation</u></p> <p>All surfaces must be dry and free of dust, dirt, oil, loose granules, gravel or peeling paint and all other foreign matter. Rusty metal must be cleaned with a wire brush and primed with a suitable primer before application of this product. Pressure washing entire surface is recommended for best results.</p>	<p>Warning! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse affects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p>