

Associated Paint, Inc.



Pro-Mix (SUPLSG)

Semi-Gloss Roof Coat—77-200DTB (Deep Tint Base) 77-300UDTB (Ultra Deep Tint Base)

Data Sheet

<u>Characteristics:</u>	<u>Specifications</u>	<u>Surface Preparation</u>
<p>Pro-Mix is formulated for Florida's tropical climate. Pro-Mix goes on easily and dries to a smooth semi-gloss finish. Pro-Mix has excellent adhesion and resists peeling, cracking, and blistering. Pro-Mix reduces under roof temperatures by reflecting heat and UV rays, saving on energy. Pro-Mix is chalk and mildew resistant, and is also lead and mercury free.</p>	<p>VOC: < 150 g/l</p> <p>Weight Solids: 44.2 ± 2% Volume Solids: 32.0 ± 2% Weight Per Gallon: 10.0 Lbs</p> <p>COVERAGE: Pro-Mix will cover up to 300 sq.ft per gallon @ 6.0 mils wet, 2.0 mils dry</p> <p>APPLICATION: Apply Pro-Mix by brush, roller or airless spray (2000 PSI and .017 tip).</p>	<p>Mildew Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the mildewed area for 10 minutes. Rinse thoroughly with water and allow the surface to dry prior to painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach water solution.</p>
<p>Vehicle Type: Latex</p>	<p>Cleanup Information</p>	<p>Warning! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse affects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p>
<p>FINISH: Semi-Gloss</p>		
<ul style="list-style-type: none"> • Cement Tile Roofs • Slate Roofs • Bahamas & Bermuda Roofs • Gravel Roofs • Clay Tile Roofs 	<p>Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral sprits.</p>	
<p>TINTING: White may be tinted to light and medium tints with universal colorants.</p>	<p>Surface Preparation</p>	
<p>77-200DTB may be tinted to deep base colors using universal colorants.</p>		<p>All surfaces must be dry and free of dust, dirt, oil, loose granules, gravel or peeling paint and all other foreign matter. Rusty metal must be cleaned with a wire brush and primed with a suitable primer before application of this product. Pressure washing entire surface is recommended for best results.</p>
<p>77-300UDTB may be tinted to ultra deep base colors using universal colorants.</p>	<p>THINNING: Not recommended. However if thinning is necessary for spray application, add no more than ½ pint of water per gallon.</p>	
<p>DRYING TIME, @ 77° F, 50% RH: Temperature & Humidity Dependent</p>	<p>Do not apply if air & surface temperature is below 50°F or if rain or heavy dew is expected within 24 hours.</p>	
<p>Touch: 45 minutes Recoat: 4 hours Flash Point: N/A</p>		