

Associated Paint, Inc.



Bond Grip.01 Bonding Primer Data Sheet

<u>Characteristics:</u>	<u>Surface Preparation</u>	<u>Surface Preparation</u>
<p>Bond-Grip is an acrylic primer formulated to provide a tie coat prior to the application of DURA-GRIP CONCRETE AND DRIVEWAY COATING. When applied over properly prepared surfaces, Bond-Grip dries quickly to give a tight bond to promote good adhesion.</p>	<p>Warning! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse affects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p>	<p>Masonry, Concrete, Cement, Block All new surfaces must be cured according to the supplier's recommendations usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. The newly cured surface should then be etched with muriatic acid as follows. Remove grease & oil with a good degreaser.</p>
<p>Vehicle Type: Acrylic</p>		<p>For stubborn stains or heavy contamination pressure cleaning is recommended. Smooth troweled or slick concrete must be etched with a solution of 1 pint muriatic acid to 1 gallon of water. Apply to concrete and allow to remain until bubbling has stopped. Flush with water. The surface should feel like sandpaper. If not, repeat etching. Be sure to flush all acid residue from surface and allow to dry.</p>
<p>FINISH: medium Sheen</p>		
<p>RECOMMENDED USES:</p> <ul style="list-style-type: none"> • Concrete • Tennis Courts • Asphalt Surfaces • Garage Floors • Patio's • Factory Floors 		
<p>TINTING:</p>		
<p>Not Recommended</p>		
<p>THINNING:</p>		
<p>Not recommended.</p>		
<p>Specifications</p>		
<p>DRYING TIME, @ 77° F, 50% RH:</p>		
<p>Temperature & Humidity Dependent</p>		
<p>Touch: 2 hours</p>		
<p>Flash Point: N/A</p>		
<p>VOC: <150 g/l</p>		
<p>Weight Solids: 20% ± 2%</p>		
<p>Volume Solids: 18% ± 2%</p>		
<p>Weight Per Gallon: 9.5 Lbs</p>		
<p>COVERAGE:</p>		
<p>Bond-Grip will cover up to 250—350 sq.ft per gallon @ 3.5 mils wet, 1.0 mils dry</p>		
<p>APPLICATION:</p>		
<p>Apply Bond-Grip by brush, roller or airless spray. (1800—2400 PSI and .017 tip)</p>		
<p></p>		
<p></p>		
<p></p>		
<p></p>		
<p></p>		
<p></p>		
<p></p>		
<p></p>		
<p></p>		
<p></p>		
<p></p>		
<p></p>		
<p></p>		
<p></p>		