

Associated Paint, Inc.



Dura-Stain.01 Concrete and Driveway Stain Data Sheet

<u>Characteristics:</u>	<u>Specifications</u>	<u>Surface Preparation</u>
<p>Dura-Stain is a premium solid hide product formulated to provide a durable, fade resistant, protective and decorative, medium-luster penetrating finish for uncoated, unsealed concrete, brick, block, pavers, kool deck, and stucco substrates. This product will color, seal, waterproof, hide color imperfections, reduce dusting and enhance the appearance of interior or exterior cementitious surfaces. Dura-Stain will not crack, peel or chip, and is highly resistant to ultra-violet rays, weather, water, and mildew.</p> <p>Vehicle Type: Acrylic - Silicone</p> <p>FINISH: Medium Sheen</p> <p>RECOMMENDED USES:</p> <ul style="list-style-type: none"> • Concrete • Garage Floors • Masonry Surfaces • Unpainted Chatahoochee • Kool Deck • Pool & Patio Decks • Stepping Stones • Walkways • Stamped Concrete • Sidewalks • Pavers • Factory Floors • Parking Garages <p>TINTING: Dura-Stain is available in most popular colors, tinting is not recommended.</p> <p>THINNING: Not recommended.</p> <p>DRYING TIME, @ 77° F, 50% RH: Temperature & Humidity Dependent</p> <p>Touch: 1 Hour Recoat: 12 Hours Flash Point: 80° F. VOC: <650 g/l</p> <p>Weight Solids: 43% ± 2% Volume Solids: 27% ± 2% Weight Per Gallon: 9.3 Lbs</p>	<p>COVERAGE: Dura-Stain will cover up to 250—350 sq.ft per gallon @ 3.0 mils wet, 1.0 mils dry</p> <p>APPLICATION: Apply Dura-Stain by brush, roller or low pressure airless spray.</p> <p>One coat is usually sufficient however if a second coat is desired, allow a minimum of 12 hours between coats.</p> <p>Important Do's & Don'ts</p> <ul style="list-style-type: none"> • Surface must be dry for 24 hours before application! • Do not apply when temperature is below 50°F or above 90°F. • Do not apply if rain or heavy dew is threatening. • Avoid heavy buildup and overlapping of Dura-Stain . • One coat is usually sufficient. However, if a second coat is desired, allow 12 hours between coats. <p>Warning! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse affects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p>	<p>All surfaces to be coated must be clean and free of moisture, efflorescence, dirt, grease, oil, chalk, mildew and any other foreign matter.</p> <ul style="list-style-type: none"> • Oils, Grease, Dirt: Scrub with TSP, detergent and/or a degreaser, rinse well & allow to dry. • Mildew & Algae: Apply a solution of 1 part bleach to 3 parts water, rinse well and allow to dry. • Efflorescence (salts): Apply a solution of 1 part muriatic acid to 3 parts water, rinse well allow to dry. <p>Sealed, painted or waxed surfaces: To allow proper penetration of Dura-Stain, all sealers, paint, etc. should be removed prior to it's application. Dura-Stain is designed for use on uncoated surfaces or over itself, however good results may be obtained when used over similar solvents (xylene, toluene thinned) acrylic type coatings/sealers. Before attempting to apply Dura-Stain over existing coatings check for adhesion and compatibility by coating a small test area. If lifting, wrinkling, excessive bubbling, slow drying, or other undesirable conditions occur, the previous coating must be completely removed.</p> <p>Steel Floated Concrete: To allow proper penetration of Wet-Look, concrete that is shiny smooth should be etched with 1 part muriatic acid to 3 parts water. Rinse well and allow to dry.</p> <p>Dura-Stain may become slippery when wet. A slip resistant additive is recommended for pedestrian areas.</p> <p>Cleanup Information</p> <p>Clean spills, spatters, hands and tools immediately after use with xylene. Follow manufacturer's safety recommendations when using xylene</p>