



Tintable Chalkboard Paint Data Sheet

<u>Characteristics:</u>	<u>Specifications</u>	<u>Surface Preparation</u>
<p>Tintable Chalkboard Paint converts most interior surfaces into a usable chalkboard. Apply to drywall, plaster, metal masonry, concrete and hardboard. Tintable Chalkboard Paint may be tinted with universal colorants to your desired color. If you choose to use Magnamagi or Active Wall magnetic receptive finishes as your primer, follow label directions for each product.</p>	<p>COVERAGE: Tintable Chalkboard Paint will cover up to 200 sq.ft per gallon.</p> <p>APPLICATION: Stir paint thoroughly until completely mixed. Apply with a 1/4" nap roller in 2 foot wide areas. Immediately go over wet paint with a foam brush to smooth out any texture. Apply at the rate of 100 sq. ft. per gallon. Two coats are recommended. Allow 2 hours between coats. Apply only when air temperature is above 60° F.</p>	<p>Mildew Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the mildewed area for 10 minutes. Rinse thoroughly with water and allow the surface to dry prior to painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach water solution.</p>
<p>Vehicle Type: Acrylic</p>	<p><u>Cleanup Information</u></p>	<p>Wood Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. Prime with high quality wood primer per labels directions.</p>
<p>FINISH: Flat</p>		<p>Drywall Fill cracks and holes with patching paste / spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust. Prime with high quality drywall primer per labels directions.</p>
<p>RECOMMENDED USES:</p> <ul style="list-style-type: none"> • Children's Rooms • Class Rooms • Meeting Rooms • Workshops • Much, much more!!! • Kitchens • Offices • Reception Areas • Conference Rooms 	<p>Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral sprits.</p>	<p>Plaster Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry. Prime with high quality plaster primer per labels directions.</p>
<p>DRYING TIME, @ 77° F, 50% RH: Temperature & Humidity Dependent</p>	<p><u>Surface Preparation</u></p>	<p>Metal: Remove all loose rust, dirt, grease and salt. Degrease surface if necessary. For Maximum adhesion on clean steel abrade surface with a course sandpaper. Rusted Metal should be primed with Prime with high quality metal primer per labels directions.</p>
<p>Touch: 30 minutes Recoat: 1 to 2 hours Flash Point: N/A</p>		<p>Warning! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse affects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p>
<p>VOC: < 50 g/l (4 lbs./gal.)</p>		
<p>Weight Solids: 48 ± 2% Volume Solids: 37 ± 2%</p>		
<p>Available on Magnamagi's website: www.magnamagic.com</p>		